Results **1** - **10** of about **14,500**. (**0.15** sec)

[PDF] DSP Data Memory Layouts Optimized for Intermediate **Address Pointer** Updates — tik.ee.ethz.ch [PDF]
B Wess, S Frohlich - Proc. APCCAS, 1998 - tik.ee.ethz.ch
... any i G { 1, 2,... , S \} defines the **program** variable vs(i) on **position** i in **...** in length, the number of distinct variables, and the number of additional **update** opportunities be **...** faster and more flexible approach to optimized data memory layout generation and **address pointer** assignment **...**
Cited by 4 - Related articles - View as HTML - All 3 versions

[CITATION] Road traffic simulation on a small computer
MH Bellby - The Computer Journal, 1972 - Br Computer Soc
... An instruction which stores the **pointer** in a specified **address** is placed in an empty unit of **...** It scans through empty road locations storing the current **address** in some specified store location until it **...** can then calculate where it will be at the end of the following **update** interval and **...**
Cited by 3 - Related articles - All 2 versions

Drawing dynamic trees
S Moen - IEEE **Software**, 1990 - ieeexplore.ieee.org
... This simple yet flexible algorithm lets you dmw compact trees for userinterface code and **update** them efficiently, July 1990 **...** The data structure has a **pointer** to the first and last line segment in each of the two polylines. **...** You must fix the **position** of the tree's root explicitly. 22 **...**
Cited by 33 - Related articles - All 7 versions

Instruction set design and optimizations for **address** computation in DSP architectures — psu.edu [PDF]
G Araujo, A Sudarsanam, S Malik - isss, 1996 - computer.org
... exists an edge (q, na) in the IG when AGU opera- tions can be used to **update** the index **...** 3(b). Each cycle correspond to a virtual **address** register (AR0 and AM). **...** 5 extracted from the DSPstone benchmark kernel $rc In this **program pointer** variables pz and ph are used to initialize **...**
Cited by 46 - Related articles - All 11 versions

Method for inserting data into a **program** at a **program position** which corresponds to a displayed cursor **position**
H Kishi, K Tanaka, T Takegahara - US Patent 4,663,705, 1987 - Google Patents
... YES **UPDATE** CURSOR DISPLAY **POSITION** IN FRAME MEMORY Page 6. **...** 6 is a block diagram of a cursor **pointer** of FIG. necessarily be created for machining performed by 3. another machine tool. **...** the X- and Y-axis **address** counters each time. **...**
Cited by 7 - Related articles

CHARMM: A **program** for macromolecular energy, minimization, and dynamics calculations — uh.cu [PDF]
BR Brooks, RE Bruccoleri, BD ... - Journal of ..., 1983 - interscience.wiley.com
... Present **address**: Noyes Laboratory of Chemical Physics, California Institute of Technology, Pasadena, California 91125. **...** (18)], and ri0 are the coordinates at the last **update** of the non **...** One choice is to maintain rigidly the **position** of certain atoms and to delete the energy terms **...**
Cited by 8133 - Related articles - All 4 versions

Guided region prefetching: a cooperative hardware/**software** approach — psu.edu [PDF]
Z Wang, D Burger, KS McKinley, SK ... - Proceedings of the ..., 2003 - portal.acm.org
... We mark a **pointer update** to be recursive if it updates itself in a loop with an object of the same data type. **...** Furthermore, each buf[i] points to a heap array, so the compiler marks it with the **pointer** hint as well. GRP will then use the **address** to prefetch the pointed-to array. **...**
Cited by 83 - Related articles - BL Direct - All 34 versions

Accessing data during the transition between **program** releases
MJ Ceruti, NS Chen - US Patent 5,896,527, 1999 - Google Patents
... 5,896,527 **update** is initiated (Action Block 401 **...** data accessing by using a starting **address** of said first indirect data accessing table as a starting **address** of an active indirect data accessing table; in said second indicate data accessing table, initializing **pointers** to unchanged **...**
Cited by 1 - Related articles

Antenna beam steering responsive to receiver and broadcast tower coordinates
JW Whitehart, DE Hadley, JE Whitecar - US Patent 6,470,186, 2002 - Google Patents
... TO STEER ANTENNA BEAM MEASURE SIGNAL STRENGTH AND COMPARE IT TO PREVIOUS **UPDATE** A1 = PREVIOUS **...** represent a steering angle 30 degrees are selected as The **position** of the **...** 3. If the table **address pointer** is initially located by having the broadcast tower **...**
Cited by 1 - Related articles

Apparatus and method for determining the Manhattan **distance** between two points
C Duong - US Patent 5,384,722, 1995 - Google Patents
... In the currently pre- functions, the **distance** computations that were referred ferred embodiment) ^j **...** 37 *** 41 "* two write ports lines of memory 30 and which **address** the contents of **...** memory 30 is uniquely coupled to the arithmetic ^ociated with the **pointer update** function, pipeline **...**
Cited by 4 - Related articles

AND update pointer address positior Search

Go to Google Home - About Google - About Google Scholar